

# 

CERAMIC WALL TILE

BEVELLED (GLOSSY & MATT)

We introduces to you a solitary gem, an amalgamation of color and exotic designs. This assemblage is sort in order to fulfill the need of the hour of both domestic and cosmopolitan market. A definite eye-turner, and eye-catching extravaganza.

### 100X 200 M

All of our products can endure harsh conditions and are long lasting as they are personally matured under stern scrutiny. Each and every design is developed under fully automatic Italian machineries. All of our best efforts are teamed together to achieve unparalleled results.

The management at We are maintaining its top game. They are highly professional, competent, and accomplished to attain the vision of making our most trusted brand in the tiles industries.

### CERAMIC WALL TILE 100X200MM

## MAGNIFIED RANGE OF EXOTIC COLLECTION

Glossy Surface

30 colors

Ignite your imagination with our extensive tile collection, featuring a glossy surface available in an astonishing palette of 30 vibrant colors. From bold and vibrant hues to subtle and soothing shades, we offer a spectrum of options to suit every design vision.

**Matt Surface** 

3 colors

Featuring a sleek matte surface available in a curated palette of 3 exquisite colors. From sophisticated neutrals to bold statements, our matte tiles offer versatile options to complement any design scheme. Elevate your space with the timeless allure of our matte finishes, adding a touch of modern elegance to your surroundings.












































SIZE 100X200MM 4X8INCH







Grey Matt White Matt

Black Matt











### TECHNICAL SPECIFICATION as per ISO 13006:2018 - ANNEXL

Sr.No.	Property	International Std.	OUR Tiles Value	Method of Testing
1	Deviation in Length and Width	± 0.6%	± 0.10%	ISO-10545-2
2	Deviation in Thickness	± 10%	± 1.88%	ISO-10545-2
3	Straightness of Sides	± 0.5%	± 0.29%	ISO-10545-2
4	Rectangularity	± 0.5%	± 0.25%	ISO-10545-2
5	Surface Flatness	± 0.5%	± 0.17%	ISO-10545-2
5	Water Absorption	>10%	12.95%	ISO-10545-3
6	MOR	MInimum 15 N/mm3	17.51 N/mm3	ISO-10545-4
7	Breaking Strength	Not less than 200 N	508.36 N	ISO-10545-4
8	Surface Quality	Minimum 95%	100%	ISO-10545-2
9	Density (g/cc)	Minimum 2.2	2.2423 g/cc	ISO-10545-3
10	Chemical Resistance	Minimum Class B	Class GA ( PASS )	ISO-10545-13
11	Crazing Resistance	2 cycle	2 cycle ( PASS ) Fully Resistance	ISO-10545-11
12	Thermal Shock Resistance	10 cycle	10 cycle ( PASS ) Fully Resistance	ISO-10545-9
13	Coefficient of Liner Thermal Expansion	Maximum 9 x 10 -6	5.45 x 10 -6	ISO-10545-8
14	Small colour differences (Plain Colour Tiles)	GL < 0.75	GL < 0.55	ISO-10545-16
15	Resistance to Staining	Min Class - 3	Class 4	ISO-10545-14
16	Resistance to Low Concentration of Acid & Alkali	Class GLA	Class GLA	ISO-10545-13
17	Resistance to Low Concentration of Acid & Alkali	Class GHA	Class GHA	ISO-10545-13
18	Household Chemical Resistance	Minimum Class B	Class GA	ISO-10545-13
19	Swimming Pool Salt	Minimum Class B	Class GA	ISO-10545-13
20	Lead and Cadmium Release	Maximum 0.1mg/dm2	0.016mg/dm2	ISO-10545-15

### PACKAGING DETAILS

SIZE	TEXTURE	THICKNESS	PIECES/BOX	SQM./BOX	SQFT./BOX	KG/BOX
100X200MM (4"X8")	BEVELLED	7.50MM	50	1.00	10.76	12.500

### Note:

- Size / shade variation is inherent in ceramic tiles, in case of any complain its should be brought to our dealer's notice before laying the tiles.
- Colour shown are indicative only. Check actual tiles for exact colour.
- The information contained in this catalogue are accurate as possible, but cannot be considered as legally binding.
- Customers are advised to inspect a sample of the tile before ordering.
- The company reserves the right to change the specifications without prior notice.















